



Illustrative picture

**SPECIFICS**

<i>Description</i>	Product type	Sloping wall sockets low voltage 50/60 Hz IP67
	Article code	<b>1269</b>
	Commercial Series	SERIES 11IEC 309 IP67

<i>General Data</i>	Poles	N° 3P+N+E	Type of material	Halogen free
	Current	A 63	Type of terminal	Allen screw
	Voltage	V~ 200/346-240/415	Terminal inlet diameter	mm 7,8
	Earth contact position	h 6	Cable sleeves diameter	mm M32-M40
	Degree of protection	IP 67	Dimensional stability	°C -25 / +70
	Impact Resistance	IK 8	Resistance glow wire test	°C +650 / +850
	Insulation Resistance	MΩ >10	Working temperature	°C -25 + 55
	Dimensions LxDxH	cm 23,2X20X11,8	Weight	kg 1,02

## Behaviour with chemical and atmospheric agents

Saline Solution	Acids		Bases		Solvents				Mineral Oil	UV rays
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Alcohol		
Resistant	Limited Resistant	Resistant	Resistant	Resistant	Limited Resistant	Limited Resistant	Resistant	Resistant	Resistant	Resistant

<i>Standards</i>	CEI EN 60309-1	CEI EN 60309-2	2014/35/UE
------------------	----------------	----------------	------------

<i>Features package</i>	<i>Descriptions</i>		<i>N/pieces</i>	<i>Weight/kg</i>
	Article		1	1,02
	Package innerbox		3	3,15
	Packaging			

<i>Dimensions</i>					<table border="1"> <thead> <tr> <th>Amp</th> <th colspan="3">63A</th> </tr> <tr> <th>Poles</th> <th>3</th> <th>4</th> <th>5</th> </tr> </thead> <tbody> <tr> <td>A</td> <td>232</td> <td>232</td> <td>232</td> </tr> <tr> <td>B</td> <td>200</td> <td>200</td> <td>200</td> </tr> <tr> <td>C</td> <td>14</td> <td>14</td> <td>14</td> </tr> <tr> <td>D</td> <td>63,5</td> <td>63,5</td> <td>63,5</td> </tr> <tr> <td>E</td> <td>136</td> <td>136</td> <td>136</td> </tr> <tr> <td>F</td> <td>134</td> <td>134</td> <td>134</td> </tr> <tr> <td>G</td> <td>102,5</td> <td>102,5</td> <td>102,5</td> </tr> <tr> <td>H</td> <td>103,5</td> <td>103,5</td> <td>103,5</td> </tr> </tbody> </table>			Amp	63A			Poles	3	4	5	A	232	232	232	B	200	200	200	C	14	14	14	D	63,5	63,5	63,5	E	136	136	136	F	134	134	134	G	102,5	102,5	102,5	H	103,5	103,5	103,5
	Amp	63A																																													
Poles	3	4	5																																												
A	232	232	232																																												
B	200	200	200																																												
C	14	14	14																																												
D	63,5	63,5	63,5																																												
E	136	136	136																																												
F	134	134	134																																												
G	102,5	102,5	102,5																																												
H	103,5	103,5	103,5																																												



Rev	Date	Technical Manager
01	7/1/20	Romano Rosi