



Illustrative picture

**SPECIFICS**

<b>Description</b>	Product type	Sloping wall socket low voltage 50/60 Hz IP44
	Article code	2535
	Commercial Series	SERIES 11 COMPACT IEC 309 IP44

<b>General Data</b>	Poles	N° 3P+E	Type of material	Halogen free
	Current	A 16	Type of terminal	Screw PH2
	Voltage	V~ 380 - 415	Terminal inlet diameter	mm 3,7
	Earth contact position	h 6	Cable sleeves diameter	mm 20
	Degree of protection	IP 44	Dimensional stability	°C -25 / +70
	Impact Resistance	IK 8	Resistance glow wire test	°C +650 / +850
	Insulation Resistance	MΩ >10	Working temperature	°C -25 + 55
	Dimensions LxDxH	cm 11x7,5x9,8	Weight	kg 0,178

## Behaviour with chemical and atmospheric agents

Saline Solution	Acids		Bases		Solvents				Mineral Oil	UV rays
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Alcohol		
Resistant	Limited Resistant	Resistant	Resistant	Resistant	Limited Resistant	Limited Resistant	Resistant	Resistant	Resistant	Resistant

<b>Standards</b>	CEI EN 60309-1	CEI EN 60309-2	2014/35/UE
------------------	----------------	----------------	------------

<b>Features package</b>	<b>Descriptions</b>		<b>N/pieces</b>	<b>Weight/kg</b>
	Article		1	0,178
	Package innerbox		10	1,87
	Packaging		./	./

<b>Dimensions</b>			<table border="1"> <tr> <td><b>Amp</b></td> <td colspan="2">16A</td> </tr> <tr> <td><b>Poles</b></td> <td>3</td> <td>4</td> </tr> <tr> <td><b>A</b></td> <td>108</td> <td>109</td> </tr> <tr> <td><b>B</b></td> <td>110</td> <td>112</td> </tr> <tr> <td><b>C</b></td> <td>60</td> <td>68</td> </tr> </table>		<b>Amp</b>	16A		<b>Poles</b>	3	4	<b>A</b>	108	109	<b>B</b>	110	112	<b>C</b>	60	68
	<b>Amp</b>	16A																	
	<b>Poles</b>	3	4																
	<b>A</b>	108	109																
<b>B</b>	110	112																	
<b>C</b>	60	68																	



Rev	Date	Technical Manager
01	7/1/20	Romano Pivi

CERTIFICATO N° 9105.RO33 - UNI EN ISO 9001:2015

Reg. A.E.E n° IT1710000010057