



Illustrative picture

SPECIFICS

Description	Product type	Panel socket angled at 10° low voltage 50/60 Hz IP44
	Article code	6001Q
	Commercial Series	SERIES 11 IEC 309 IP44

General Data	Poles	N° 2P+E	Type of material	Halogen free
	Current	A 16	Type of terminal	Screw PH2
	Voltage	V~ 200-250	Terminal inlet diameter	mm 3,7
	Earth contact position	h 6		
	Degree of protection	IP 44	Dimensional stability	°C -25 /+70
	Impact Resistance	IK 8	Resistance glow wire test	°C +650 / +850
	Insulation Resistance	MΩ >10	Working temperature	°C -25 + 55
	Dimensions LxDxH	cm 76X46X87	Weight	kg 0,115

Behaviour with chemical and atmospheric agents											
Saline Solution	Acids		Bases		Solvents				Mineral Oil	UV rays	
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Alcohol			
Resistant	Limited Resistant	Resistant	Resistant	Resistant	Limited Resistant	Limited Resistant	Resistant	Resistant	Resistant	Resistant	

Standards	CEI EN 60309-1	CEI EN 60309-2	2014/35/UE
-----------	----------------	----------------	------------

Features package	Descriptions		N/pieces	Weight/kg
	Article		1	0,115
	Package innerbox		10	1,24
	Packaging		150	19,22

Dimensions			<table border="1"> <thead> <tr> <th rowspan="2">Amp Poles</th> <th colspan="3">16A</th> <th colspan="3">32A</th> </tr> <tr> <th>3</th> <th>4</th> <th>5</th> <th>3</th> <th>4</th> <th>5</th> </tr> </thead> <tbody> <tr> <td>A</td> <td>85</td> <td>85</td> <td>85</td> <td>95</td> <td>95</td> <td>98</td> </tr> <tr> <td>B</td> <td>75</td> <td>75</td> <td>75</td> <td>80</td> <td>80</td> <td>80</td> </tr> <tr> <td>C</td> <td>60</td> <td>60</td> <td>60</td> <td>70</td> <td>70</td> <td>70</td> </tr> <tr> <td>D</td> <td>60</td> <td>60</td> <td>60</td> <td>60</td> <td>60</td> <td>60</td> </tr> <tr> <td>E</td> <td>5.2</td> <td>5.2</td> <td>5.2</td> <td>5.5</td> <td>5.5</td> <td>5.5</td> </tr> <tr> <td>F</td> <td>47</td> <td>47</td> <td>47</td> <td>54</td> <td>54</td> <td>56</td> </tr> <tr> <td>G</td> <td>60</td> <td>68</td> <td>76</td> <td>81</td> <td>81</td> <td>88</td> </tr> </tbody> </table>						Amp Poles	16A			32A			3	4	5	3	4	5	A	85	85	85	95	95	98	B	75	75	75	80	80	80	C	60	60	60	70	70	70	D	60	60	60	60	60	60	E	5.2	5.2	5.2	5.5	5.5	5.5	F	47	47	47	54	54	56	G	60	68	76	81	81	88
	Amp Poles	16A			32A																																																																	
3		4	5	3	4	5																																																																
A	85	85	85	95	95	98																																																																
B	75	75	75	80	80	80																																																																
C	60	60	60	70	70	70																																																																
D	60	60	60	60	60	60																																																																
E	5.2	5.2	5.2	5.5	5.5	5.5																																																																
F	47	47	47	54	54	56																																																																
G	60	68	76	81	81	88																																																																



CERTIFICATO N° 9105.RO33 - UNI EN ISO 9001:2015

Reg. A.E.E n° IT17100000010057

Rev	Date	Technical Manager
01	7/1/20	Romano Pivi



Illustrative picture

SPECIFICS

<i>Description</i>	Product type	Panel socket angled at 10° low voltage 50/60 Hz IP44
	Article code	6004Q
	Commercial Series	SERIES 11 IEC 309 IP44


<i>General Data</i>	Poles	N° 2P+E	Type of material	Halogen free
	Current	A 32	Type of terminal	Screw PH2
	Voltage	V~ 200-250	Terminal inlet diameter	mm 4,6
	Earth contact position	h 6		
	Degree of protection	IP 44	Dimensional stability	°C -25 /+70
	Impact Resistance	IK 8	Resistance glow wire test	°C +650 / +850
	Insulation Resistance	MΩ >10	Working temperature	°C -25 + 55
	Dimensions LxDxH	cm 8x6,2x9,5	Weight	kg 0,187

Behaviour with chemical and atmospheric agents										
Saline Solution	Acids		Bases		Solvents				Mineral Oil	UV rays
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Alcohol		
Resistant	Limited Resistant	Resistant	Resistant	Resistant	Limited Resistant	Limited Resistant	Resistant	Resistant	Resistant	Resistant

<i>Standards</i>	CEI EN 60309-1	CEI EN 60309-2	2014/35/UE
------------------	----------------	----------------	------------

<i>Features package</i>	<i>Descriptions</i>		<i>N/pieces</i>	<i>Weight/kg</i>
	Article		1	0,187
	Package innerbox		5	1,025
	Packaging		75	15,995

<i>Dimensions</i>			<table border="1"> <thead> <tr> <th>Amp</th> <th colspan="3">16A</th> <th colspan="3">32A</th> </tr> <tr> <th>Poles</th> <th>3</th> <th>4</th> <th>5</th> <th>3</th> <th>4</th> <th>5</th> </tr> </thead> <tbody> <tr> <td>A</td> <td>85</td> <td>85</td> <td>85</td> <td>95</td> <td>95</td> <td>98</td> </tr> <tr> <td>B</td> <td>75</td> <td>75</td> <td>75</td> <td>80</td> <td>80</td> <td>80</td> </tr> <tr> <td>C</td> <td>60</td> <td>60</td> <td>60</td> <td>70</td> <td>70</td> <td>70</td> </tr> <tr> <td>D</td> <td>60</td> <td>60</td> <td>60</td> <td>60</td> <td>60</td> <td>60</td> </tr> <tr> <td>E</td> <td>5,2</td> <td>5,2</td> <td>5,2</td> <td>5,5</td> <td>5,5</td> <td>5,5</td> </tr> <tr> <td>F</td> <td>47</td> <td>47</td> <td>47</td> <td>54</td> <td>54</td> <td>56</td> </tr> <tr> <td>G</td> <td>60</td> <td>68</td> <td>76</td> <td>81</td> <td>81</td> <td>88</td> </tr> </tbody> </table>						Amp	16A			32A			Poles	3	4	5	3	4	5	A	85	85	85	95	95	98	B	75	75	75	80	80	80	C	60	60	60	70	70	70	D	60	60	60	60	60	60	E	5,2	5,2	5,2	5,5	5,5	5,5	F	47	47	47	54	54	56	G	60	68	76	81	81	88
	Amp	16A			32A																																																																		
Poles	3	4	5	3	4	5																																																																	
A	85	85	85	95	95	98																																																																	
B	75	75	75	80	80	80																																																																	
C	60	60	60	70	70	70																																																																	
D	60	60	60	60	60	60																																																																	
E	5,2	5,2	5,2	5,5	5,5	5,5																																																																	
F	47	47	47	54	54	56																																																																	
G	60	68	76	81	81	88																																																																	



CERTIFICATO N° 9105.RO33 - UNI EN ISO 9001:2015

Reg. A.E.E. n° IT17100000010057