



Illustrative picture

SPECIFICS

<i>Description</i>	Product type	Panel socket angled at 10° low voltage 50/60 Hz IP44
	Article code	6002Q
	Commercial Series	SERIES 11 IEC 309 IP44

<i>General Data</i>	Poles	N° 3P+E	Type of material	Halogen free
	Current	A 16	Type of terminal	Screw PH2
	Voltage	V~ 380-415	Terminal inlet diameter	mm 3,7
	Earth contact position	h 6		
	Degree of protection	IP 44	Dimensional stability	°C -25 /+70
	Impact Resistance	IK 8	Resistance glow wire test	°C +650 / +850
	Insulation Resistance	MΩ >10	Working temperature	°C -25 + 55
	Dimensions LxDxH	cm 76X46X87	Weight	kg 0,135

Behaviour with chemical and atmospheric agents										
Saline Solution	Acids		Bases		Solvents				Mineral Oil	UV rays
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Alcohol		
Resistant	Limited Resistant	Resistant	Resistant	Resistant	Limited Resistant	Limited Resistant	Resistant	Resistant	Resistant	Resistant

<i>Standards</i>	CEI EN 60309-1	CEI EN 60309-2	2014/35/UE
------------------	----------------	----------------	------------

<i>Features package</i>	<i>Descriptions</i>		<i>N/pieces</i>	<i>Weight/kg</i>
	Article		1	0,135
	Package innerbox		10	1,44
	Packaging		150	22,22

<i>Dimensions</i>		<table border="1"> <thead> <tr> <th rowspan="2">Amp Poles</th> <th colspan="3">16A</th> <th colspan="3">32A</th> </tr> <tr> <th>3</th> <th>4</th> <th>5</th> <th>3</th> <th>4</th> <th>5</th> </tr> </thead> <tbody> <tr> <td>A</td> <td>85</td> <td>85</td> <td>85</td> <td>95</td> <td>95</td> <td>98</td> </tr> <tr> <td>B</td> <td>75</td> <td>75</td> <td>75</td> <td>80</td> <td>80</td> <td>80</td> </tr> <tr> <td>C</td> <td>60</td> <td>60</td> <td>60</td> <td>70</td> <td>70</td> <td>70</td> </tr> <tr> <td>D</td> <td>60</td> <td>60</td> <td>60</td> <td>60</td> <td>60</td> <td>60</td> </tr> <tr> <td>E</td> <td>5,2</td> <td>5,2</td> <td>5,2</td> <td>5,5</td> <td>5,5</td> <td>5,5</td> </tr> <tr> <td>F</td> <td>47</td> <td>47</td> <td>47</td> <td>54</td> <td>54</td> <td>56</td> </tr> <tr> <td>G</td> <td>60</td> <td>68</td> <td>76</td> <td>81</td> <td>81</td> <td>88</td> </tr> </tbody> </table>	Amp Poles	16A			32A			3	4	5	3	4	5	A	85	85	85	95	95	98	B	75	75	75	80	80	80	C	60	60	60	70	70	70	D	60	60	60	60	60	60	E	5,2	5,2	5,2	5,5	5,5	5,5	F	47	47	47	54	54	56	G	60	68	76	81	81	88
	Amp Poles	16A			32A																																																											
3		4	5	3	4	5																																																										
A	85	85	85	95	95	98																																																										
B	75	75	75	80	80	80																																																										
C	60	60	60	70	70	70																																																										
D	60	60	60	60	60	60																																																										
E	5,2	5,2	5,2	5,5	5,5	5,5																																																										
F	47	47	47	54	54	56																																																										
G	60	68	76	81	81	88																																																										



CERTIFICATO N° 9105.RO33 - UNI EN ISO 9001:2015

Reg. A.E.E n° IT17100000010057

Rev	Date	Technical Manager
01	7/1/20	Romano Rivi



Illustrative picture

SPECIFICS

Description	Product type	Panel socket angled at 10° low voltage 50/60 Hz IP44
	Article code	6005Q
	Commercial Series	SERIES 11 IEC 309 IP44

General Data	Poles	N° 3P+E	Type of material	Halogen free
	Current	A 32	Type of terminal	Screw PH2
	Voltage	V~ 380-415	Terminal inlet diameter	mm 4,6
	Earth contact position	h 6	Dimensional stability	°C -25 /+70
	Degree of protection	IP 44	Resistance glow wire test	°C +650 / +850
	Impact Resistance	IK 8	Working temperature	°C -25 + 55
	Insulation Resistance	MΩ >10	Weight	kg 0,204
	Dimensions LxDxH	cm 8x6,2x9,5		

Behaviour with chemical and atmospheric agents

Saline Solution	Acids		Bases		Solvents				Mineral Oil	UV rays
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Alcohol		
Resistant	Limited Resistant	Resistant	Resistant	Resistant	Limited Resistant	Limited Resistant	Resistant	Resistant	Resistant	Resistant

Standards	CEI EN 60309-1	CEI EN 60309-2	2014/35/UE
-----------	----------------	----------------	------------

Features package	Descriptions		N/pieces	Weight/kg
	Article		1	0,204
	Package innerbox		5	1,11
	Packaging		75	17,27

Dimensions		<table border="1"> <thead> <tr> <th rowspan="2">Amp Poles</th> <th colspan="3">16A</th> <th colspan="3">32A</th> </tr> <tr> <th>3</th> <th>4</th> <th>5</th> <th>3</th> <th>4</th> <th>5</th> </tr> </thead> <tbody> <tr> <td>A</td> <td>85</td> <td>85</td> <td>85</td> <td>95</td> <td>95</td> <td>98</td> </tr> <tr> <td>B</td> <td>75</td> <td>75</td> <td>75</td> <td>80</td> <td>80</td> <td>80</td> </tr> <tr> <td>C</td> <td>60</td> <td>60</td> <td>60</td> <td>70</td> <td>70</td> <td>70</td> </tr> <tr> <td>D</td> <td>60</td> <td>60</td> <td>60</td> <td>60</td> <td>60</td> <td>60</td> </tr> <tr> <td>E</td> <td>5.2</td> <td>5.2</td> <td>5.2</td> <td>5.5</td> <td>5.5</td> <td>5.5</td> </tr> <tr> <td>F</td> <td>47</td> <td>47</td> <td>47</td> <td>54</td> <td>54</td> <td>56</td> </tr> <tr> <td>G</td> <td>60</td> <td>68</td> <td>76</td> <td>81</td> <td>81</td> <td>88</td> </tr> </tbody> </table>	Amp Poles	16A			32A			3	4	5	3	4	5	A	85	85	85	95	95	98	B	75	75	75	80	80	80	C	60	60	60	70	70	70	D	60	60	60	60	60	60	E	5.2	5.2	5.2	5.5	5.5	5.5	F	47	47	47	54	54	56	G	60	68	76	81	81	88
	Amp Poles	16A			32A																																																											
3		4	5	3	4	5																																																										
A	85	85	85	95	95	98																																																										
B	75	75	75	80	80	80																																																										
C	60	60	60	70	70	70																																																										
D	60	60	60	60	60	60																																																										
E	5.2	5.2	5.2	5.5	5.5	5.5																																																										
F	47	47	47	54	54	56																																																										
G	60	68	76	81	81	88																																																										



CERTIFICATO N° 9105.ROS3 - UNI EN ISO 9001:2015

Reg. A.E.E n° IT17100000010057

Rev	Date	Technical Manager
01	7/1/20	Piemonte Rosi