



Illustrative picture

**SPECIFICS**

<b>Description</b>	Product type	Movable plug low voltage 50/60 Hz IP67
	Article code	9162
	Commercial Series	SERIES 10 IEC 309 IP67

<b>General Data</b>	Poles	N° 3P+N+E	Type of material	Halogen free
	Current	A 63	Type of terminal	Allen screw
	Voltage	V~ 200/346-240/415	Terminal inlet diameter	mm 7,8
	Earth contact position	h 6	Cable clamp tightening capacity	mm 14,5 - 36
	Degree of protection	IP 67	Dimensional stability	°C -25 /+70
	Impact Resistance	IK 8	Resistance glow wire test	°C +650 / +850
	Insulation Resistance	MΩ >10	Working temperature	°C -25 + 55
	Dimensions LxDxH	cm 26,1x10,3x10,3	Weight	kg 0,72

Behaviour with chemical and atmospheric agents											
Saline Solution	Acids		Bases		Solvents				Mineral Oil	UV rays	
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Alcohol			
Resistant	Limited Resistant	Resistant	Resistant	Resistant	Limited Resistant	Limited Resistant	Resistant	Resistant	Resistant	Resistant	

<b>Standards</b>	CEI EN 60309-1	CEI EN 60309-2	2014/35/UE
------------------	----------------	----------------	------------

<b>Features package</b>	<b>Descriptions</b>		<b>N/pieces</b>	<b>Weight/kg</b>
	Article		1	0,72
	Package innerbox		10	7,29
	Packaging		.	.

<b>Dimensions</b>		<b>Amp</b>	63A		
		<b>Poles</b>	3	4	5
		<b>A</b>	256	256	256
		<b>B</b>	114	114	114
		<b>C</b>	75	75	75
		<b>D</b>	14.5-36	14.5-36	14.5-36



CERTIFICATO N° 9105.RO33 - UNI EN ISO 9001:2015



Reg. A.E.E n° IT17100000010057



Rev	Date	Technical Manager
01	7/1/20	Romano Pivi

Illustrative picture

**SPECIFICS**

<i>Description</i>	Product type	Industrial plugs
	Article code	<b>9187</b>
	Commercial Series	MOVABLE PLUGS

<i>General Data</i>	Poles	N° 3P+N+E		
	Current	A 125	Type of terminal	Allen screw
	Voltage	V~ 200-346/240-415		
	Earth contact position	h 6	Cable clamp tightening capacity	mm 14,5 - 36
	Degree of protection	IP 67	Dimensional stability	°C -25 /+70
	Impact Resistance	IK 8	Resistance glow wire test	°C +650 / +850
	Insulation Resistance	MΩ >10	Working temperature	°C , -25 + 55
	Dimensions LxDxH	cm 32x15x15	Weight	kg 1,18

Behaviour with chemical and atmospheric agents										
Saline Solution	Acids		Bases		Solvents				Mineral Oil	UV rays
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Alcohol		
Resistant	Limited Resistant	Resistant	Resistant	Resistant	Limited Resistant	Limited Resistant	Resistant	Resistant	Resistant	Resistant

<i>Standards</i>	CEI EN 60309-1	CEI EN 60309-2	2014/35/UE
------------------	----------------	----------------	------------

<i>Features package</i>	<i>Descriptions</i>		<i>N/pieces</i>	<i>Weight/kg</i>
	Article		1	1,18
	Package innerbox		10	2,45
	Packaging			

<i>Dimensions</i>	
-------------------	--



CERTIFICATO N° 9105.RO3 - UNI EN ISO 9001:2015

Reg. A.E.E n° IT17100000010057

