

Product data sheet

HDS338B12Q710

Characteristics

Magnetic starter, HDS3-38, 10 A, 380/400 V, 50/60 Hz, plastic



Main

| | |
|-------------------------------------|--|
| Range of product | HDS3 |
| Product or component type | Enclosed DOL starter |
| Device application | Motor control Motor protection |
| Device composition | HDC3 contactor HDR3s thermal overload relay |
| Thermal protection adjustment range | 7...10 A |
| Motor power hp | 3.0 hp at 240 V AC 50/60 Hz 5.5 hp at 380/400 V AC 50/60 Hz 5.5 hp at 440 V AC 50/60 Hz 7.5 hp at 660/690 V AC 50/60 Hz |
| Motor power kW | 2.2 kW at 240 V AC 50/60 Hz 4.0 kW at 380/400 V AC 4.0 kW at 440 V AC 5.5 kW at 660/690 V AC |

Complementary

| | |
|------------------------------|---|
| Housing material | Plastic |
| Utilisation category | AC-3 |
| [Uc] control circuit voltage | 380/400 V AC 50/60 Hz |
| Control type | Push-button start green I Push-button stop/reset red O |
| Width | 115 mm |
| Height | 203 mm |
| Depth | 129 mm |

Environment

| | |
|---------------------------------------|---------------|
| IP degree of protection | IP54 |
| Standards | IEC 60947-4-1 |
| Quality labels | CE |
| Ambient air temperature for operation | -5...40 °C |