

218.3236

PLUG
32A 3P+E 6h 380-415V 60Hz 50Hz
Screw terminals



EN 60309-1 (1999)
EN 60309-2 (1999)
EN 60309-1/A1 (2007)
EN 60309-1/A2 (2012)
EN 60309-2/A1 (2007)
EN 60309-2/A2 (2012)

Low voltage direct. 2014/35/EU

Commercial Series

OPTIMA Series

Synthetical description

PLUG

Mounting version

PORTABLE

■ TECHNICAL CHARACTERISTICS

Rated current	32A
Poles	3P+E
Hour position	6h
Rated voltage (range)	250-400V
Rated voltage	380-415V
Working frequency	60Hz
	50Hz
Terminals	Screw terminals

■ PHYSICAL CHARACTERISTICS

Mounting version	PORTABLE
Colour	RED
Material	THERMOPLASTIC
Protection degree	Watertight
Protection degree IP	IP66/IP67/IP69
Protection degree IK	IK08
Types of available outlets	STRAIGHT
Contact material	CuZn (brass)
Surface treatment contacts	Nickel-plated
Cable entry	CABLE GLAND

■ DOWNLOAD

[Technical drawing \[PDF\]](#)
[Technical drawing \[DWG\]](#)
[Technical drawing \[STP\]](#)