

313.1647**CONNECTOR**

16A 3P+N+E 6h 346-415V 50Hz 60Hz

Screw terminals



EN 60309-1 (1999)
 EN 60309-2 (1999)
 EN 60309-1/A1 (2007)
 EN 60309-1/A2 (2012)
 EN 60309-2/A1 (2007)
 EN 60309-2/A2 (2012)

Low voltage direct. 2014/35/EU

Commercial Series

OPTIMA Series

Synthetical description

CONNECTOR

Mounting version

PORTABLE

■ TECHNICAL CHARACTERISTICS

Rated current	16A
Poles	3P+N+E
Hour position	6h
Rated voltage (range)	250-400V
Rated voltage	346-415V
Working frequency	50Hz
	60Hz
Terminals	Screw terminals

■ PHYSICAL CHARACTERISTICS

Mounting version	PORTABLE
Colour	RED
Material	THERMOPLASTIC
Protection degree	Splash proof
Protection degree IP	IP44/IP54
Protection degree IK	IK08
Types of available outlets	STRAIGHT
Contact material	CuZn (brass)
Cable entry	CABLE GLAND

■ DOWNLOAD

Technical drawing [PDF]
 Technical drawing [DWG]
 Technical drawing [STP]

313.3247**CONNECTOR**

32A 3P+N+E 6h 346-415V 50Hz 60Hz
Screw terminals



EN 60309-1 (1999)
EN 60309-2 (1999)
EN 60309-1/A1 (2007)
EN 60309-1/A2 (2012)
EN 60309-2/A1 (2007)
EN 60309-2/A2 (2012)

Low voltage direct. 2014/35/EU

Commercial Series

OPTIMA Series

Synthetical description

CONNECTOR

Mounting version

PORTABLE

■ TECHNICAL CHARACTERISTICS

Rated current	32A
Poles	3P+N+E
Hour position	6h
Rated voltage (range)	250-400V
Rated voltage	346-415V
Working frequency	50Hz
	60Hz
Terminals	Screw terminals

■ PHYSICAL CHARACTERISTICS

Mounting version	PORTABLE
Colour	RED
Material	THERMOPLASTIC
Protection degree	Splash proof
Protection degree IP	IP44/IP54
Protection degree IK	IK08
Types of available outlets	STRAIGHT
Contact material	CuZn (brass)
Cable entry	CABLE GLAND

■ DOWNLOAD

[Technical drawing \[PDF\]](#)
[Technical drawing \[DWG\]](#)
[Technical drawing \[STP\]](#)

318.6347**CONNECTOR**

63A 3P+N+E 6h 346-415V 60Hz 50Hz

Mantle terminals



EN 60309-1 (1999)
EN 60309-2 (1999)
EN 60309-1/A1 (2007)
EN 60309-1/A2 (2012)
EN 60309-2/A1 (2007)
EN 60309-2/A2 (2012)

Low voltage direct. 2014/35/EU

Commercial Series

OPTIMA Series

Synthetical description

CONNECTOR

Mounting version

PORTABLE

■ TECHNICAL CHARACTERISTICS

Rated current	63A
Poles	3P+N+E
Hour position	6h
Rated voltage (range)	250-400V
Rated voltage	346-415V
Working frequency	60Hz
	50Hz
Terminals	Mantle terminals

■ PHYSICAL CHARACTERISTICS

Mounting version	PORTABLE
Colour	RED
Material	THERMOPLASTIC
Protection degree	Watertight
Protection degree IP	IP66/IP67/IP69
Protection degree IK	IK08
Types of available outlets	STRAIGHT
Contact material	CuZn (brass)
Cable entry	CABLE GLAND

■ DOWNLOAD

[Technical drawing \[PDF\]](#)
[Technical drawing \[DWG\]](#)
[Technical drawing \[STP\]](#)

■ OPTIONS & VARIOUS NOTES

Notes	EASY-PLUG
-------	-----------