

515.12557

SURFACE MOUNTING SOCKET
125A 3P+N+E 6h 346-415V 50Hz
60Hz Screw terminals



EN 60309-1 (1999)
EN 60309-2 (1999)
EN 60309-1/A1 (2007)
EN 60309-2/A1 (2007)
Low voltage direct. 2014/35/EU

Commercial Series

OPTIMA Series

Synthetical description

SURFACE MOUNTING SOCKET

Mounting version

FLUSH/SURFACE MOUNTING

■ TECHNICAL CHARACTERISTICS

Rated current	125A
Poles	3P+N+E
Hour position	6h
Rated voltage (range)	250-400V
Rated voltage	346-415V
Working frequency	50Hz
	60Hz
Terminals	Screw terminals

■ PHYSICAL CHARACTERISTICS

Mounting version	FLUSH/SURFACE MOUNTING
Colour	RED
Material	THERMOPLASTIC
Protection degree	Watertight
Protection degree IP	IP66/IP67
Protection degree IK	IK08
Types of available outlets	ANGLED
Contact material	CuZn (brass)
Cable entry	PG 48

■ DOWNLOAD

[Technical drawing \[PDF\]](#)
[Technical drawing \[DWG\]](#)
[Technical drawing \[STP\]](#)