

**518.6357T****SURFACE MOUNTING SOCKET****63A 3P+N+E 6h 346-415V 60Hz 50Hz****Mantle terminals**

EN 60309-2/A1 (2007)

EN 60309-1 (1999)

EN 60309-2 (1999)

EN 60309-1/A1 (2007)

EN 60309-1/A2 (2012)

EN 60309-2/A2 (2012)

Low voltage direct. 2014/35/EU

**Commercial Series****OPTIMA-TOP Series****Synthetical description****SURFACE MOUNTING SOCKET****Mounting version****SURFACE MOUNTING****■ TECHNICAL CHARACTERISTICS**

|                       |                  |
|-----------------------|------------------|
| Rated current         | 63A              |
| Poles                 | 3P+N+E           |
| Hour position         | 6h               |
| Rated voltage (range) | 250-400V         |
| Rated voltage         | 346-415V         |
| Working frequency     | 60Hz             |
|                       | 50Hz             |
| Terminals             | Mantle terminals |

**■ PHYSICAL CHARACTERISTICS**

|                            |                  |
|----------------------------|------------------|
| Mounting version           | SURFACE MOUNTING |
| Colour                     | RED              |
| Material                   | THERMOPLASTIC    |
| Protection degree          | Watertight       |
| Protection degree IP       | IP66/IP67/IP69   |
| Protection degree IK       | IK08             |
| Types of available outlets | ANGLED           |
| Contact material           | CuZn (brass)     |
| Cable entry                | M40X1,5          |

**■ DOWNLOAD**[Technical drawing \[PDF\]](#)[Technical drawing \[DWG\]](#)[Technical drawing \[STP\]](#)