

522.1657**SURFACE MOUNTING SOCKET****16A 3P+N+E 6h 346-415V 50Hz 60Hz****Screw terminals**

EN 60309-1/A2 (2012)

EN 60309-1 (1999)

EN 60309-2 (1999)

EN 60309-1/A1 (2007)

EN 60309-2/A1 (2007)

EN 60309-2/A2 (2012)

Low voltage direct. 2014/35/EU

Commercial Series

OPTIMA Series

Synthetical description

SURFACE MOUNTING SOCKET

Mounting version

SURFACE MOUNTING

■ TECHNICAL CHARACTERISTICS

Rated current	16A
Poles	3P+N+E
Hour position	6h
Rated voltage (range)	250-400V
Rated voltage	346-415V
Working frequency	50Hz
	60Hz
Terminals	Screw terminals

■ PHYSICAL CHARACTERISTICS

Mounting version	SURFACE MOUNTING
Colour	RED
Material	THERMOPLASTIC
Protection degree	Splash proof
Protection degree IP	IP44/IP54
Protection degree IK	IK08
Types of available outlets	STRAIGHT
Contact material	CuZn (brass)
Cable entry	DRILLING POINT MARK

■ DOWNLOAD[Technical drawing \[PDF\]](#)[Technical drawing \[DWG\]](#)[Technical drawing \[STP\]](#)

522.3257

SURFACE MOUNTING SOCKET
32A 3P+N+E 6h 346-415V 50Hz 60Hz
Screw terminals



EN 60309-1/A2 (2012)
EN 60309-1 (1999)
EN 60309-2 (1999)
EN 60309-1/A1 (2007)
EN 60309-2/A1 (2007)
EN 60309-2/A2 (2012)

Low voltage direct. 2014/35/EU

Commercial Series

OPTIMA Series

Synthetical description

SURFACE MOUNTING SOCKET

Mounting version

SURFACE MOUNTING

■ TECHNICAL CHARACTERISTICS

Rated current	32A
Poles	3P+N+E
Hour position	6h
Rated voltage (range)	250-400V
Rated voltage	346-415V
Working frequency	50Hz
	60Hz
Terminals	Screw terminals

■ PHYSICAL CHARACTERISTICS

Mounting version	SURFACE MOUNTING
Colour	RED
Material	THERMOPLASTIC
Protection degree	Splash proof
Protection degree IP	IP44/IP54
Protection degree IK	IK08
Types of available outlets	STRAIGHT
Contact material	CuZn (brass)
Cable entry	DRILLING POINT MARK

■ DOWNLOAD

Technical drawing [PDF]
Technical drawing [DWG]
Technical drawing [STP]