

522.1653

SURFACE MOUNTING SOCKET
16A 2P+E 6h 200-250V 50Hz 60Hz
Screw terminals



UK
CA

EN 60309-2/A1 (2007)
EN 60309-2 (1999)
EN 60309-1/A1 (2007)
EN 60309-1/A2 (2012)
EN 60309-2/A2 (2012)

Low voltage direct. 2014/35/EU

Commercial Series

OPTIMA Series

Synthetical description

SURFACE MOUNTING SOCKET

Mounting version

SURFACE MOUNTING

■ TECHNICAL CHARACTERISTICS

Rated current	16A
Poles	2P+E
Hour position	6h
Rated voltage (range)	200-250V
Rated voltage	200-250V
Working frequency	50Hz
	60Hz
Terminals	Screw terminals

■ PHYSICAL CHARACTERISTICS

Mounting version	SURFACE MOUNTING
Colour	BLUE
Material	THERMOPLASTIC
Protection degree	Splash proof
Protection degree IP	IP44/IP54
Protection degree IK	IK08
Types of available outlets	STRAIGHT
Contact material	CuZn (brass)
Cable entry	DRILLING POINT MARK

■ DOWNLOAD

Technical drawing [PDF]
Technical drawing [DWG]
Technical drawing [STP]

522.3253

SURFACE MOUNTING SOCKET
32A 2P+E 6h 200-250V 50Hz 60Hz
Screw terminals



UK
CA

EN 60309-1/A2 (2012)
EN 60309-1 (1999)
EN 60309-2 (1999)
EN 60309-1/A1 (2007)
EN 60309-2/A1 (2007)
EN 60309-2/A2 (2012)

Low voltage direct. 2014/35/EU

Commercial Series	OPTIMA Series
Synthetical description	SURFACE MOUNTING SOCKET
Mounting version	SURFACE MOUNTING

■ TECHNICAL CHARACTERISTICS

Rated current	32A
Poles	2P+E
Hour position	6h
Rated voltage (range)	200-250V
Rated voltage	200-250V
Working frequency	50Hz
	60Hz
Terminals	Screw terminals

■ PHYSICAL CHARACTERISTICS

Mounting version	SURFACE MOUNTING
Colour	BLUE
Material	THERMOPLASTIC
Protection degree	Splash proof
Protection degree IP	IP44/IP54
Protection degree IK	IK08
Types of available outlets	STRAIGHT
Contact material	CuZn (brass)
Cable entry	DRILLING POINT MARK

■ DOWNLOAD

[Technical drawing \[PDF\]](#)
[Technical drawing \[DWG\]](#)
[Technical drawing \[STP\]](#)