

VSR-05



SSR-05D



SSR-09



SSR-19



LIQUID LEVEL RELAYS

Product Code	Description	Dimensions (mm)	220V AC (50/60 Hz)	3 x 380V AC (50 Hz) + Neutral	< 100k Ω Setting	< 50k Ω Fixed	High - Low Voltage	Phase Sequence	Delay for Upper Electrode	Fixed Asymmetry	Package Quantity
SSR-05D	Liquid Level Relay (With microprocessor)	CLASSIC BOX									12
VSR-05	Liquid Level Relay	V-AUTOMAT									20
VSR-05-24	Liquid Level Relay with 24V Supply	V-AUTOMAT									10
SSR-09	Liquid Level Relay for Steam Iron Boilers (Without Tank)	CLASSIC BOX									10
SSR-19	Liquid Level Relay for Steam Iron Boilers (With Tank)	CLASSIC BOX									10

SSE-10	Liquid Level Electrode (Stainless)
FLT-1.6	Cable Floater, 1.6 meters, 8A 250V AC (50/60 Hz), IP68
FLT-3	Cable Floater, 3 meters, 8A 250V AC (50/60 Hz), IP68
FLT-5	Cable Floater, 5 meters, 8A 250V AC (50/60 Hz), IP68
FLT-10	Cable Floater, 10 meters, 8A 250V AC (50/60 Hz), IP68



FLT SERIES

SSE-10



HYDROPHORE SEQUENCING RELAYS

NEW

HSR-S



HSR-02X



HSR-03X



Product Code	Description	Dimensions (mm)	Thermal	2 Pressure Switch Input	3 Pressure Switch Input	2 Booster Outputs	3 Booster Outputs	Rail Type	Package Quantity
HSR-S	Smart Hydrophore Sequencing Relay (with Adjustable Co-Aging)	DIN TYPE							
HSR-02X	Hydrophore Sequencing Relay	DIN TYPE							20
HSR-03X	Hydrophore Sequencing Relay	DIN TYPE							15

PHOTOCELL RELAYS

Product Code	Description
FTV-04	Photocell Relay, V-Automat DIN Body, 1 - 10 Lux adjustable, 5A / 250V AC relay output
FT-GR	Photocell Relay, 10 Lux fixed, 7A / 250V AC relay output
FT-G	Photocell Eye, (5 mm LDR)



FTV-04



FT-GR



FT-G