




FJ16N/D



FJ35NL/D



FJ35NH/D

CERTIFICATION	CB/CE/UKCA/RoHS	
MATERIAL		
Size(mm)	12.2x42.5x54	
Screw	Zinc-Coated Steel	
Pressure Frame	Tin-Coated Brass	
Conductor	Tin-Coated Brass	
Housing	PA66/V-0	
ELECTRICAL DATA		
Standards	IEC 60947-7-2	UL 1059
Voltage(V)	-	-
Current(A)	101	-
WIRING DATA		
Strip Length(mm)	11	
Flexible Wire(mm ²)	4~16	
Rigid Wire(mm ²)	2.5~25	
Imperial Wire(AWG)	14~4	
Clamping Screw:		
Thread/Torque(N·m)	M4/1.5~1.8	
Fixing Screw:		
Thread/Torque(N·m)	M4/1.5~1.8	
PACKING		
Pcs/Inner Box	50	
Pcs/Master Carton	850	
Marking Tag		
ZB12	Pcs/Bag	100

CERTIFICATION	CB/CE/UKCA/RoHS	
MATERIAL		
Size(mm)	15.2x55x51	
Screw	Zinc-Coated Steel	
Pressure Frame	Tin-Coated Brass	
Conductor	Tin-Coated Brass	
Housing	PA66/V-0	
ELECTRICAL DATA		
Standards	IEC 60947-7-2	UL 1059
Voltage(V)	-	-
Current(A)	125	-
WIRING DATA		
Strip Length(mm)	16	
Flexible Wire(mm ²)	0.75~35	
Rigid Wire(mm ²)	0.75~35	
Imperial Wire(AWG)	18~2	
Clamping Screw:		
Thread/Torque(N·m)	M6/3.2~3.7	
Fixing Screw:		
Thread/Torque(N·m)	M5/2.5~3	
PACKING		
Pcs/Inner Box	32	
Pcs/Master Carton	544	
Marking Tag		
ZB15	Pcs/Bag	100

CERTIFICATION	CB/CE/UKCA/RoHS	
MATERIAL		
Size(mm)	15x50x62	
Screw	Zinc-Coated Steel	
Pressure Frame	Tin-Coated Brass	
Conductor	Tin-Coated Brass	
Housing	PA66/V-0	
ELECTRICAL DATA		
Standards	IEC 60947-7-2	UL 1059
Voltage(V)	-	-
Current(A)	150	-
WIRING DATA		
Strip Length(mm)	15	
Flexible Wire(mm ²)	0.75~35	
Rigid Wire(mm ²)	0.75~50	
Imperial Wire(AWG)	18~0	
Clamping Screw:		
Thread/Torque(N·m)	M6/3.2~3.7	
Fixing Screw:		
Thread/Torque(N·m)	M5/2.5~3	
PACKING		
Pcs/Inner Box	24	
Pcs/Master Carton	408	
Marking Tag		
ZB15	Pcs/Bag	100