

Voltage Detectors

Safety

Medium voltage detector - Outdoor

VTE

*High resolution voltage detector with pole
Medium Voltage - Optical & Acoustic*

Electronic voltage detector with micro controller and direct contact detection. New advanced technology acquisition that guarantees a perfect and safe indication even in conflicting electric field environments.

Voltage presence is indicated by high luminosity red LED and high acoustic pressure buzzer.

Voltage absence is indicated by high luminosity green LED.

Low battery is indicated by orange LED.

Self-checking system for its complete circuit by pressing test button.

Stops working when low battery.

Work temperature range: from -25°C to +55°C.

Self-ignition when voltage presence.

Auto turn-off into sleep mode after two minutes of voltage absence.

In this mode consumption is less than 1 µA.

Power supply: 9 V alkaline battery, type 6LR61 (included).

Indoor and outdoor use by appropriate insulating pole to the detector voltage range.

Connection to the pole by Universal head.

Supplied with carrying bag for pole and metallic box to store and transport the voltage detector with battery included.

Manufactured according to IEC 61243:2003+A1:2009 and UNE-EN 61243-1:2006+A1:2011 standards (except voltage range).



VOLTAGE RANGES

from 5 to 35 or 5 to 66 kV

31002 VTE-U

Code	Ref.	Voltage ranges	Frequency
641113	VTE-5/36-U	from 5 to 36 kV	50 / 60 Hz
641115	VTE-5/66-U	from 5 to 66 kV	

31002 VTE-P

Code	Ref.	Voltage ranges	Frequency	Insulating pole length
641103	VTE-5/36-P	from 5 to 36 kV		1.30 m
641105	VTE-5/66-P	from 5 to 66 kV	50 / 60 Hz	2 m

* Insulating pole included.

Optical / Acoustic

