



Morsetti a serraggio rapido per cavi rigidi
Push-in connectors for rigid wires

Certificazioni: UL, FIMKO Conformità: CE, RoHS 2015/863/UE Normative: EN 60998-1:2004 Materiale guscio: Policarbonato e poliammide Materiale inserto: Rame Elettrolitico Temperatura d'esercizio: -5°C +85°C Resistenza al calore: 130°C			Approvals: UL, FIMKO Compliance: CE, RoHS 2015/863/UE Standards: EN 60998-1: 2004 Shell material: Polycarbonate and Polyamide Insert material: Electrolytic Copper Working temperature: -5°C +85°C Heat resistance: 130°C			 			
Articolo Item	N. fori N. holes	Colore inserti lateral Lateral inserts color	Tensione Nominale Rated voltage	Grado di protezione Protection degree	Corrente nominale Rated current	Conduttori rigidi Rigid conductors	Dimensioni Dimensions		
							A mm	B mm	C mm
BIS252	2	Rosso Red	450 V	IP20	32 A	2 x 1÷2,5 mm²	19	10	9
BIS253	3	Arancione Orange	450 V	IP20	32 A	3 x 1÷2,5 mm²	19	13	9
BIS254	4	Giallo Yellow	450 V	IP20	32 A	4 x 1÷2,5 mm²	19	17	9
BIS255	5	Grigio Grey	450 V	IP20	32 A	5 x 1÷2,5 mm²	19	21	9
BIS258	8	Nero Black	450 V	IP20	32 A	8 x 1÷2,5 mm²	19	17	17

MINIBOX morsetti a serraggio rapido per cavi rigidi
MINIBOX push-in connectors for rigid wires

Certificazioni: VDE, KEMA Conformità: CE, RoHS 2015/863/UE Normative: EN 60998-1:2004 Materiale guscio: Poliammide Materiale inserto: Rame Elettrolitico Temperatura d'esercizio: -40°C +100°C Resistenza al calore: 140°C			Approvals: VDE, KEMA Compliance: CE, RoHS 2015/863/UE Standards: EN 60998-1: 2004 Shell material: Polyamide Insert material: Electrolytic Copper Working temperature: -40°C +100°C Heat resistance: 140°C						
									
Articolo Item	N. fori N. holes	Colore Color	Tensione Nominale Rated voltage	Grado di protezione Protection degree	Corrente nominale Rated current	Conduttori rigidi Rigid conductors	Dimensioni Dimensions		
							A mm	B mm	C mm
BIR253	3	Grigio Grey	450 V	IP20	32 A	3 x 1÷2,5 mm²	19	15	9
BIR254	4		450 V	IP20	32 A	4 x 1÷2,5 mm²	19	19	9
BIR255	5		450 V	IP20	32 A	5 x 1÷2,5 mm²	19	22	9